BLIND RIVETERS

Blind Riveter (Heavy Duty)



Heavy-duty riveter installs and sets smooth mandrel steel, aluminum, copper or brass domed and countersunk rivets. Furnished with four interchangeable nosepieces in sizes 3/32, 1/8, 5/32 and 3/16". Comes with an assortment of aluminum and steel rivets and a wrench for attaching the pulling heads. The riveter automatically regrips the mandrel for greater pull. The handles are springloaded and cushioned. The riveter comes in an impact-resistant metal case with operating instructions, and a rivet selection chart is fastened inside the case. Overall length is 10". NOTE: This riveter does not set Monel rivets. Creative Engineering P/N 2006 K, Marson P/N HP-2.

5120·01·289·4310 EA \$30.02

Blind Riveter Kit

Install 3/32-, 1/8-, 5/32-, 3/16- and 1/4"-diameter universal or countersunk blind rivets and No. 6 through 3/8"-diameter blind rivet nuts with this kit. Hand-operated riveter features hydraulic power and continuous operation and provides 4000 lb of pulling force; measures 10" long, 6-3/4" high and 2-3/4" thick and weighs 1-1/2 lb. Includes a 6"-long handle with vinyl handgrips; 1/8, 3/16 and 1/4" nosepieces; a 1/8" nutplate nosepiece; No. 6, 8, 10 (TSN), 1/4 (TSN), 5/16 and 3/8" driving anvils; master shaft; turn nut; adapter sleeve; and adapter puller. Includes $6 \cdot 32$, $8 \cdot 32$, $10 \cdot 32$, $1/4 \cdot 28$, $10 \cdot 24$, $1/4 \cdot 20$, $5/16 \cdot 18$ and $3/8 \cdot 16$ pull-up studs. Comes in a metal box.

Pulling heads are not included. Fastening Systems International P/N D-100 MIL-1 or equal.

5180·01·201·4978 KT \$419.48


Pulling heads are included. heads are right angle, offset and extended straight. Fastening Systems International P/N D-100 MIL-2 or equal.

5180·01·201·4979 KT \$1298.61

You may fax your order to us 24 hours a day, 7 days a week.

RIVET CUTTERS

Rivet Cutter



Pincer-type cutter is for use on aluminum rivets with universal or countersunk heads. Has a 1/16- to 1/4"-diameter capacity; with length gauges 1/4 to 3/4" in 1/16" increments. Measures 16" long overall and 6" wide in the open position. Weighs 2-1/2 lb. ATI P/N AT501S or equal.

5110-00-180-2892 EA \$89.30

HANDSAWS

Bow Saw



Use bow saw for pruning and landscaping. Saw features a tubular-steel frame and a hardened-steel blade with a blade guard. Frame has either a tension clamping lever or a screw and wing nut device to facilitate blade alignment and replacement. Blade has two or more cutting teeth per each racker and is 36" long and 1" wide.

5110-00-340-3276 EA \$11.58

Crosscut Saw

Crosscut saw is for cutting wood across grain. Features a hardwood handle and a hardened and tempered taper ground blade. Blade is tapered in width and has spring-set and bevel-filed teeth. GGG-S-65.

Has a straight, steel blade with eight points per inch. Blade measures 26" long, 5-3/4" wide at butt and 1-1/2" wide at point.

26" x 8 point/in. straight-back crosscut hand saw.

5110.00.293.3435 EA \$16.32

Crosscut saw is for cutting wood across grain. Features a hardwood handle and ahardened and tempered taper ground blade. Blade is tapered in width and has spring-set and bevel-filled teeth. GGG-S-65.

Has a straight, steel blade with eight points per inch

5110-00-142-4999 24" length, 5-3/8" width at butt, 1-1/4" width at point EA **\$14.17**